


PRODUCT DATA SHEET



Features:

Standard open frame rack equipped with 19" format mounting posts.

U shaped rails 3"x1 1/4"tapped both front and rear with EIA compliant RMS space.

Meets or Exceeds EIA-310D Standards.

Base with holes for floor anchoring.

All mounting posts are clearly with RU space markings.

Adjustable depth from 24"-36".

Available accessories include: Fixed and sliding shelves, keyboard shelves, cable managers, PDUs and others.

Stocked in 28U and 45U heights; other height from 16U to 47U can be special ordered. Flat package for inventory space saving and lower transportation cost.

Standards:

Complies with ANSI/EIA RS-310-D, IEC297-2, DIN41491; PART1, DIN41494; PART7, GB/3047.2-92 standards.

Material:

SPCC cold rolled steel

Load Capacities:

16U-22U Static Loading Capacity: 300kg 25U-45U Static Loading Capacity: 600kg

Degree of Protection:

lp20

Thickness of Steel:

Mounting: 1.8mm Base Angle: 3.0mm Top Angle: 3.0mm Adjustable Space Bar: 1.8mm

Surface treatment:

Degreasing, pickling, phosphoric, dip-coat primed, powder coat.

Colors options:

Standard: RAL9004/9005 BLACK. Available in RAL7035-COMPUTER GRAY and RAL9010-CREAM WHITE by special order.

Ordering information:

Part Number	Height	RUs	Color
NTFR4PXXSTBK	7 FT	45	BLACK
NTFR4PXXSTBK	4 FT	28	BLACK





