



## Features and Functions

### Professional and Reliable

- New logical and visualized GUI design
- Dual-OS design to ensure high reliability of system running
- ANR technology to enhance the storage reliability when the network is disconnected

### Video Input and Transmission

- Adopt stream over TLS encryption technology (enhanced SDK service and RTP over HTTPS protocol) which provides more secure stream transmission service (max. 128 Mbps TLS stream outgoing bandwidth)
- Up to 32-ch IP cameras can be connected (up to 12 MP)
- Connectable to the third-party network cameras

### Compression and Recording

- H.265+ compression effectively reduces the storage space by up to 75%
- Full channel recording at up to 12MP resolution

### HD Video Output

- HDMI and VGA independent outputs provided
- HDMI Video output at up to 4K (3840 × 2160) resolution

### Storage and Playback

- Up to 4 SATA interfaces connectable for HDD connection
- 8/16-ch synchronous playback at up to 1080p resolution
- Important files management
- HDD health monitoring

### Smart &POS Function

- Supports multiple VCA (Video Content Analytics) events
- Smart search for the selected area in the video; and smart playback to improve the playback efficiency
- Supports VCA search for fire/ship/temperature/temperature difference detection triggered video files
- POS information overlay on live view and playback
- POS triggered recording and alarm


### Network & Ethernet Access

- Hik-Connect for easy network management
- Gigabit Ethernet network interface
- 8/16 independent PoE network interfaces are provided
- Long distance (100-300 m) network transmission via PoE

## Specifications

Model	XR-432	
Video/Audio input	IP video input	32-ch Up to 12 MP resolution
	Two-way audio	1-ch, RCA (2.0 Vp-p, 1 k Ω)
Network	Incoming bandwidth	256 Mbps
	Outgoing bandwidth	256 Mbps
	Remote connection	128
Video/Audio output	Recording resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA /4CIF /DCIF/ 2CIF/CIF/QCIF
	CVBS output (Optional)	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
	HDMI output resolution	4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
	VGA output resolution	1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
	Audio output	1-ch, RCA (Linear, 1 KΩ)
Decoding	Decoding format	H.265/H.265+/H.264/H.264+/MPEG4
	Live view / Playback resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF /DCIF/ 2CIF/CIF/QCIF
	Synchronous playback	16-ch
	Capability	2-ch @ 12 MP (20fps) / 4-ch @ 8 MP (25fps) / 8-ch @ 4MP (30fps) / 16-ch @ 1080p (30fps)
Network management	Network protocols	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS
Hard disk	SATA	4 SATA interfaces for 4HDDs
	Capacity	Up to 10TB capacity for each HDD
External interface	Network interface	1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
	Serial interface	1 RS-485 (half-duplex), 1 RS-232
	USB interface	Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0
	Alarm in/out	16/4
POE Interface	Interface	16 RJ-45 10/100 Mbps self-adaptive Ethernet interfaces
	Power	≤200W
	Supported standard	IEEE 802.3 af/at
General	Power supply	100 to 240 VAC
	Power	≤300 W
	Consumption (without hard disk)	≤20 W (without enabling PoE)
	Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Working humidity	10 to 90 %
	Dimensions (W × D × H)	445 × 400 × 71 mm ( 17.5"× 15.7" × 2.8")
	Weight (without hard disk)	≤ 5 kg (11 lb)

## Physical Interfaces



Index	Description	Index	Description
1	LAN1 and LAN2 Interfaces	7	VGA Output (DB9 Connector)
2	AUDIO OUT	8	RS-485 Serial Interface
3	AUDIO IN	9	Controller Port, Alarm In/Alarm Out
4	HDMI Interface	10	GND
5	USB 3.0 Interface	11	100 to 240 VAC power supply
6	RS-232 Serial Interface	12	Power Switch